

**RPSEA Unconventional Gas Conference 2011: Technical Keys to
Unlocking Additional Reserves**

Sustaining Fracture Area and Conductivity of Gas Shale Reservoirs for Enhancing Long-Term Production and Recovery

**Hugo Morales and Roberto Suarez-Rivera, TerraTek
Dr. Ahmad Ghassemi, Texas A&M**

April 19-20, 2011



Why This Project ?

Motivation

Over the past ten years there has been a revolution related to gas production from shale reservoirs. Industry analysts estimate shale gas to account for half the natural gas production in North America by 2020.

Challenge

Only a fraction of the wells in tight gas shale reservoirs show sustained long term production. The balance, are characterized by marginal production and fast declining rates.

Theorem

Operational experience leads to the hypothesis that in regions of high reservoir quality (1) loss of fracture conductivity and (2) loss of fracture area are among the main factors leading to marginal production.


Project Goal

Provide solutions leading to increase production and recoverable gas reserves by targeting three main subjects:

- 1. Material characterization**
- 2. Loss of productive fracture surface area, and**
- 3. Loss in fracture conductivity**

Study conducted on three shale plays: Barnett, Haynesville, and Marcellus


Material Characterization: Rock Quality Index (RQI)



HRA – Heterogeneous Rock Analysis

Completion Quality Index (CQI)

HRA selects rock classes with similar properties throughout the well



Core data:
Young's Modulus
Poisson's Ratio
In-Situ Stresses
UCS



Each rock class classified by its Completion Quality Index (CQI)




Petrologic Properties




Barnett



Haynesville





Marcellus





XRD – Matrix Mineralogical Contents



Barnett



Haynesville




Marcellus







Quartz (Grey); Clay (Brown); Calcite (Cream); Other (Purple)





Mobile Fluid Saturations







Barnett




Haynesville




Marcellus



Mechanical Properties - Notation




Static Test
Stress Strain Envelope




Dynamic Test
P and S velocities

Mechanical Properties - Notation






**Vertical
Sample cut normal to
bedding plane**






**Horizontal
Sample cut parallel to
bedding plane**

Mechanical Properties - Dynamic




Barnett



Haynesville




Marcellus




V_p and V_s are compression and shear velocities

Mechanical Properties - Observations




Wave velocities: Slower for good and faster for poor quality rock classes



Young's modulus: Smaller for good and larger for poor quality rock classes.

Anisotropy: Good rock class - higher anisotropy ($E_h/E_v \sim 2/1$); poor rock class - lower anisotropy ($E_h/E_v \sim 1$)*






Poisson's ratio: Smaller for good and larger for poor quality rock classes.

In-Situ stress: Smaller for good and larger for poor quality rock classes.



* Fracture width underestimated by using E_h only

Mechanical Properties - Static




Barnett



Haynesville




Marcellus




Fracture Conductivity Tests

Objective – Simulate effects of:

- (1) Fracture roughness,
- (2) changes in proppant mesh size, and
- (3) changes in temperature in creep tests



Test	Pressure	Temp.	Fracture	Proppant
1	500 – 10000 psi	70 °F	Saw Cut	N
2	500 – 10000 psi	70 °F	Brazil	N
3	500 – 10000 psi	70 °F	Saw Cut	40/70
4	500 – 10000 psi	70 °F	Saw Cut	100
5	500 – 10000 psi	70 °F	Saw Cut	100 & 40/70
6	5000 psi	70 °F	Saw Cut	100
7	5000 psi	140 °F	Saw Cut	100





Samples – Best reservoir quality Barnett

Fracture Roughness Effects



Saw cut



Brazil Fracture



Saw cut (smooth surface) results: Negligible fracture conductivities less than 0.01 md-ft. Used as reference for sensitivity tests.

Brazil fracture (rough surface) results: Fracture conductivities from 13.5 to 0.001 md-ft. About 0.2 md-ft at Barnett in-situ conditions

Mixing Proppant Effects





Mixing proppant sizes objective: Improve long term conductivity by controlling embedment; allowing the larger proppants offset embedment of smaller ones.

Was the objective achieved?


Average embedment was lowest; and normalized fracture conductivity (right plot) shows: With stress increase, fracture conductivity surpasses the other conductivities

Embedment Values



Digital microscopic images showing embedment craters for test with mixed proppant sizes (left) and average embedment for all tests with proppant (right)


Creep Effects



Constant stress creep response:

Loading - instantaneous elastic strain (ϵ_0), and delayed creep strain.

Unloading - elastic strain dissipates immediately; creep strain dissipates gradually to a residual or zero strain.



Fracture conductivity results:

Most of the decline (15% and 40% loss) occurred within the first 5 hours of testing. No significant decrease in fracture conductivity afterwards.

Large embedment of comparable magnitude to the tests where pressure was ramped. Temperature significantly decreases fracture conductivity.

Creep Tests Images




Pre and post pictures for creep test



Digital image of post test proppant showing about 10% proppant crushing .



Fracture Modeling



Eclipse production modeling of complex fracture networks indicate:



- 1 Fracture conductivity changes in primary fractures have insignificant effect on production.
- 2 Fracture conductivity changes in tertiary fractures have significant effect on production.

Fracture Observations from Cores




- 1 Offset at tips of collinear fractures
- 2 Induced fracture growth controlled by calcite filled natural fractures (a and b)
- 3 Merging of collinear fractures (c)

Fracture Observations from Cores




- 1 Parallel fractures connected by a horizontal (shear) fracture
- 2 Induced fracture intercepting a calcite filled natural fracture (b)

Fracture Observations from Cores



Images showing micro fractures



Induced fracture tends to follow weak paths along filled natural fractures

Conclusions: Mechanical Properties

- **Wave velocities:** Slower for good and faster for poor quality rock classes
- **Young's modulus:** Smaller for good and larger for poor quality rock classes.
- **Anisotropy:** Good rock class - higher anisotropy ($E_h/E_v \sim 2/1$); poor rock class - lower anisotropy ($E_h/E_v \sim 1$)
- **Poisson's ratio:** Smaller for good and larger for poor quality rock classes.
- **In-Situ stress:** Smaller for good and larger for poor quality rock classes.

Conclusions: Fracture Conductivity Tests

- Fractures with asperities (Brazil Test) provide small conductivity – less than 0.2 md-ft at typical closure pressures for the Barnett reservoir.
- Conductivity for tests with mixed proppant sizes (100 & 40/70) provide longer sustained production as corroborated by the lowest embedment and conductivity surpassing companion tests.
- Creep tests showed that loss in fracture conductivity happen within the first few hours of testing.
- Temperature effects significantly decrease the fracture conductivity.

Conclusions: Fracture Modeling

- Fracture conductivity changes in primary fractures have insignificant effect on production.
- Fracture conductivity changes in tertiary fractures have significant effect on production.

Acknowledgments



Partners inspecting shale cores on the 2010 review meeting

- RPSEA
- Shell Exploration and Production,
- Encana Oil & Gas, and
- Pennsylvania General Energy Company.

Project Tasks

- Task 1 – Project management plan
- Task 2 – Technology status assessment
- Task 3 – Material property characterization
- Task 4 – Loss of fracture area in fracture networks
- Task 5 – Conductivity of un-propped fractures on core
- Task 6 – Conductivity of propped fractures on core
- Task 7 – Integration of loss of effective surface area and conductivity in fracture networks and degradation of fracture conductivity
- Task 8 – Field testing of Tasks 4 to 7
- Task 9 – Roadmap for reservoir characterization and production and recovery maximization
- Task 10 – Technology transfer